

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
8 April 2004 (08.04.2004)


PCT

(10) International Publication Number  
**WO 2004/030119 A2**

- (51) International Patent Classification<sup>7</sup>: **H01M**
- (21) International Application Number:  
PCT/US2003/031236
- (22) International Filing Date:  
30 September 2003 (30.09.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
60/414,848 30 September 2002 (30.09.2002) US
- (71) Applicant (for all designated States except US): **E.I. DU PONT DE NEMOURS AND COMPANY** [US/US]; 1007 Market Street, Wilmington, DE 19898 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **KUMAR, Sridhar** [CA/US]; 2 Salina Court, Hockessin, DE 19707 (US). **ABDOU, Mohamed** [CA/US]; 16 Masters Way, Chadds Ford, PA 19317 (US). **XIE, Tuyu** [CA/CA]; 944 Nottingham Avenue, Kingston, Ontario K7P 2B8 (CA). **ANDRIN, Peter** [CA/CA]; 34 Sarah Street, Napanee, Ontario K7R 3X4 (CA).
- (74) Agent: **FICKES, Daphne, P.**; E.I. du Pont de Nemours and Company, Legal Patent Records Center, 4417 Lancaster Pike, Wilmington, DE 19805 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: METHOD FOR REGENERATION OF PERFORMANCE IN A FUEL CELL



(57) **Abstract:** A process for improved performance in a fuel cell or stack of fuel cells wherein the fuel cell has a cathode, an anode, an anode chamber, a cathode chamber, a fuel comprising an anolyte that flows through the cell, and a catholyte gas, and wherein the fuel cell is connected to an external load, and wherein the process comprises taking the load off the cell, and cycling between a minimum voltage and about 50% of the maximum voltage drawn from the fuel cell until a maximum current is reached, or a minimum load and about 50% of the maximum load until a maximum voltage is reached. Fuel cell performance is further enhanced by purging.

WO 2004/030119 A2